AS-380

Auto Chemistry Analyzer

Technical specifications

General information

Machine type	Random access, open reagent & locked reagent (optional)
Test speed	Constant 300 tests/hour (Mono reagent or double reagent)
Test principle	Colorimetric method, turbidimetry
Test method	1 point end, 2 point end, Fixed-Time, Kinetics
Calibration type	Linear & nonlinear

Sample unit

Sample tray	70 sample positions
Sample tube	Micro cup & test tube & blood collection tube can be used. (Φ 12 -13)mm * (25 – 100)mm
Sample volume	2-30μL, step by 0.1μL
Sample probe	Liquid surface detection, timely tracking for liquid volume. Collision avoidance
Sample barcode	Sample barcode reader (optional)

Reagent unit

Reagent tray	70 reagent positions , Non-stop cooling system with peltier pad inside, 24 hours 2℃-14℃, open system, could accept any reagent.
Reagent volume	20-300μl, step by 1μl
Reagent needle	Liquid surface detection, timely tracking for liquid volume. Collision avoidance.
Regent barcode	Regent barcode reader (optional)

Reaction unit

Reaction tray	90 reaction cuvettes, new amorphous optical plastics reaction cups, perfect transmittance.
Reaction volume	150μl-330μl
Reaction time	10 minutes
Temperature	Peltier pad incubation system, reaction temperature (37℃ ± 0.1 ℃)

Mixing system

Mixer	paddle-type mixing, effective reducing of carry-over

Optical system

Light source	Halogen lamp
Wavelength	340nm; 405nm; 450nm; 505nm; 546nm; 578nm; 630nm; 700nm(4 more options)
Absorbance range	0-4.0 Abs
Resolution	0.0001 Abs

Operating system

Operation system	Windows XP, Windows 7, Windows 8, Windows 10
Data processing	Automatic calibration, test combination, effective time management of reagents, serum index, whole process detection, linear expansion of enzyme, blank deduction,dirty cuvette memory , cross infection prevention, patient information memory and association input, automatic report audit, data fuzzy query, report statistics and printing, reference range grading, alarm information classification, user operation privilege classification management.
Report printing	6 formats optional, surpport custom pattern
interface	TCP/IP network interface


Working conditions

Power supply	AC 110/220V ± 10%, 50/60 Hz, 650W
Water consumption	12L/hour(maximum)
Dimension	910mm * 650mm * 1120mm(L*W*H)
Weight	127.5kg

I.M.D Laboratoires

Illustrations non conventionnelles I.M.D Laboratoires se réserve le droit de modifier à tout moment et sans préavis les informations contenues dans ce document destiné aux professionnels de la santé. Ce document contient des informations destinées à être diffusées largement et peut en conséquence ne pas contenir tous les détails et informations sur les produits.
Lire attentivement les instructions figurant dans les notices et manuels des instruments et réactifs.
© 2024 **SARL Innovation Médicale et Diagnostic de Laboratoires** / 22 RN n°11, BP n°121, Ain Benian, Alger, Algérie
TEL : +213 23 39 83 79 +213 23 39 83 80 +213 23 39 84 43 / **FAX** : +213 23 39 83 81
EMAIL : commandes.clients@imdlaboratoires.com www.imdlaboratoires.com

I.M.D Laboratoires



AS-380

Auto Chemistry Analyzer

300 Tests/Hour, Double Reagent

I.M.D Laboratoires

BIOELAB

AS-380


Auto Chemistry Analyzer

- Constant 300 test / hour with double reagent
- 70 reagent positions
- Automatic liquid level sensing, anti-collision protection.
- Integrated full closed optical system, multi wavelength simultaneous detection.
- New amorphous optical plastics reaction cups, perfect transmittance.
- Maintenance free semiconductor solid state refrigeration
- Friendly surface and easy to operation
- 5-stage, 2 times automatic washing system，Alkaline cleaning solution



Multifunctional precision sampling probe

- External & internal mirror polish, external & internal probe washing
- Dedicated sampling probe equipped with sensitive liquid sensor, timely feedback of reagent & sample residuals
- Collision protection, automatic probe depth adjusting




Excellent mixer design

- Teflon coating mixer. No water dropping (reducing carry-over)
- Excellent mixing effect with standard mixing procedure




High precision ceramic syringe

- Permanent ceramic piston
- Accurate dispensing as low as 0.1 µl



Reagent & sample tray

- 70 reagent positions
- 70 sample positions, micro cup & test tube can be used
- Non-stop cooling system with peltier pad inside, 24 hours 2℃-14℃
- Bar code reader(optional)



Reaction tray

- 90 reaction cuvettes
- Reaction volume as low as 150 µl
- Stable & accurate temperature(37±0.1 ℃) for reaction



Advanced operating system

- User friendly software interface simple, easy-to-operation
- Sample automatic dilution(decrease, increase, normal)
- Reaction result automatic checking and warning, calibration result automatic checking, warning alarm log
- Linear & nonlinear calibration,Multi-points calibration up to 8 points
- Quality control apply to westgard, L-T plot, cumulative

